

## PATH TO THE FUTURE

Der MSI MAG 274QFDE E20 Gaming-Monitor, 27 Zoll atemberaubendes Rapid IPS, 2560 x 1440 (WQHD) und 200Hz für ultra-flüssige Bilder. Perfekt für wettbewerbsorientierte Spieler, die nach Immersion suchen.



## SELLING POINTS

- Rapid IPS Panel – Bietet eine Reaktionszeit von 0,5 ms (GtG, min.) und optimiert Bildschirmfarben und Helligkeit.
- 200Hz Bildwiederholrate – Reagiere schneller dank flüssigerer Bildwiedergabe.
- 0.5ms (GtG, Min.) Reaktionszeit – Eliminiert Bildrisse und ruckelnde Bildraten.
- AI Vision – Die neue AI-Vision-Technik kann nicht nur Details in dunklen Bereichen sichtbar machen, sondern auch die Gesamthelligkeit erhöhen und Farben intensiver gestalten.
- Less Blue Light – Reduziere die Lichtemission im blau-violetten Bereich des Blaulichtspektrums.



1. 5-Wege Joystick Navigation
2. DisplayPort 1.4a (HBR3)
3. 2x HDMI™ 2.0b (WQHD@144Hz)
4. Kopfhörerausgang
5. Stromanschluss
6. Kensington lock

**SPECIFICATION**

Model	SKU Number	9S6-3CE41H-068
	Entity MKT Name	MAG 274QFDE E20
	Part No	9S6-3CE41H-068
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	596.736(H) x 335.664(V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.2331(H)x0.2331(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	NVIDIA G-SYNC Compatible / AMD FreeSync™ Premium
	Dynamic Refresh Rate Activated Range	48~200Hz
	HDR (High dynamic range)	VESA DsiplayHDR 400
	SDR Brightness (nits)	300
	HDR Brightness (Peak nits)	400
	Contrast Ratio	1200:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	71.51~298 KHz(H) / 48~200 Hz(V)
	Refresh Rate	200HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	105%/91%
	NTSC (CIE1931 area percentage/overlap)	90%/85%
	sRGB (CIE1976 area percentage/overlap)	121%/97%
	sRGB (CIE1931 area percentage/overlap)	128%/99%
	Adobe RGB (CIE1976 area percentage/overlap)	103%/93%
	Adobe RGB (CIE1931 area percentage/overlap)	95%/89%
	DCI-P3 (CIE1976 area percentage/overlap)	96%/92%
	DCI-P3 (CIE1931 area percentage/overlap)	94%/91%
	Rec.709 (CIE1976 area percentage/overlap)	121%/97%
	Rec.709 (CIE1931 area percentage/overlap)	128%/99%
	Rec.2020 (CIE1976 area percentage/overlap)	70%/70%
	Rec.2020 (CIE1931 area percentage/overlap)	67%/67%
	Surface Treatment	Anti-glare
Display Colors	1.07B	
Color bit	10 bits (8 bits + FRC)	
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.4a (HBR3)
	DisplayPort HDCP version	2.3
Garantie	Warranty	36 Monate Pick-Up & Return
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C13	

Zubehör	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	613.5 x 249.7 x 439.05
	Product Dimension without Stand (WxDxH) (mm)	613.5 x 62.08 x 362.5
	Stand Dimension (WxDxH) (mm)	339.81 x 249.71 x 143.02
	Weight (Net kg)	4.9
	Weight Without Stand (kg)	4.4
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	68.3 x 12.7 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	69.8 x 14 x 46.7
	Weight (Gross kg)	6.9
Barcode Info	EAN	4711377392419